



BE SEEN - BE SAFE

TF 510 Series Beacon

2 in 1 Beacon

- Flashing Hazard Warning
- Torch (Worklight) Function

Body Color:	Yellow
LED Color Options:	8 x Red / 3 x White Worklight
Candela:	30 Red / 200 White
No of LED's:	8 / 3 Worklight
Flash Rate:	165 - 185 fpm
Battery Type:	D Cell x 2 (Not included)
Battery Life:	40 hours
Weight:	450g inc Batteries
Height:	20 cm



E-flare™ Protector Beacon

www.eflarecorp.com

1. Always use quality alkaline **D** cells.
2. Install new batteries with **+** terminals towards lens. Do not mix types.
3. Make sure cap is tightened as far as possible to engage O-ring.
4. To switch beacon on, rotate lens clockwise; off, counter-clockwise.
5. Stand beacon vertical in base on a firm surface, or use cone mount clip.
6. Replace batteries when yellow LED indicator lights up.




Cone Mount Clip

Attaches to any Eflare Beacon to enable vertical positioning of the beacon on most types of cones.



Magnetic Clip

Attaches to any Eflare Beacon.
Not suitable for moving vehicles.



Suction Clip

Attaches to any Eflare Beacon for use on all smooth surfaces.
Not suitable for moving vehicles.



Daylight Hood

Attaches to any 500 Series Eflare Beacon.
For limiting spread of light beam.



Rubber Base Mount

General purpose mount for all Eflare Beacons.



Aviation Base Mount

Secure mount for special purposes.



Magnetic Base Mount

Combined Magnetic Base and Cap.
Can be used with any Eflare Beacon.
Rated to 80 KPH when securely mounted on vehicle.



Floatation Collar

Fits any 500 series beacon.
Provides reliable self-righting buoyancy for marine use.

Other product information
available from our website
www.eflarecorp.com

Distributed by: